

PSMU MAINTENANCE UNITS

- 600 Gal Capacity with 35 GPM Hydraulically Driven Pump
- 14 HP Water Cooled Diesel Engine
- 8' Fully Circulating Spraybar with Solvent Tank
- Adjustable Application Rate Control



Precision Spray Maintenance Units

WEIGHTS		Model PSMU-600	
Axle(s)	Tandem	Tank Heads	7 gauge, Dished & Flanged, Welded Inside & Out
Axle Capacity	6,000 lbs each	Tank Shell	10 gauge, Standard Oval Cross Section
Capacity	600 gal	Baffle	7 gauge with Crawl Hole
		Manhole	20 in
		Contents Gauge	Yes 100 gal Increments
		Tank Insulation	2 in Rock Wool (Option)
DIMENSIONS		ENGINE	
Overall Length	155 in	Manufacturer	Kubota
Overall Width	96 in	Fuel Type	Diesel
Loading Height	83 in	HP (SAE/1394)	14 HP
Tires	(4) 225/75R15	Type and Cooling	Electric Start, Water Cooled
Brakes	Electric	FLUID CAPACITIES	
PERFORMANCE DATA		Solvent Tank	9 gal
Asphalt Pump	30 GPM, Reversible	Hydraulic Tank	9 gal
Heating, w/ Thermostat	Hydraulic Driven	Diesel Burner Tank	9 gal
Heating Flue	Diesel, 250,000 BTU	TRAILER, SAFETY	
Hand Spray Wand	Single, 8 in Diameter	Hitch	2 3/4 in Pintle Eye
Hand Spray Hose	Single Nozzle	Braking	Electronic Break-Away System with Safety Chains
Hand Spray Hose Reel	40 foot	Wiring	Trailer Lighting, Standard
Spray Bar	Manual Wind	OPTIONAL EQUIPMENT	
	8 foot, Recirculating	Skid Mounting, Ball Hitch in lieu of Pintle Eye, Fire Extinguisher, Tank Insulation	
	with key fob control	on PSMU-600, Electric Overnight Heat, Special Paint	
Thermometer Type	Dial, 50° - 550° F	Spray Bar Extensions, Double or Tripple Overlap Spray Bar	
	Pencil Thermometer, Optional		
Pump Drive	Hydrostat Control		
Nozzle Actuation	Hydraulic		
Nozzle Spacing	On 16 in Centers		

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

Sold & Serviced by:



Calder Brothers Corporation

250 E. Warehouse Ct.

Taylors, SC 29687

Phone (864) 244-4800

Fax (864) 244-5007

www.CalderBrothers.com